

O.D.	Length	Pcs/Bdl	Feet/Bdl	Bdl. Per Master	Feet/Bdl Master	Type K & K-OXY		Type L		Type M		Type DWV		O.D.	Type L-ACR	
						Wt/Bdl lbs.	Wt. Per Master	Wt/Bdl lbs.	Wt. Per Master	Wt/Bdl lbs.	Wt. Per Master	Wt/Bdl lbs.	Wt. Per Master		Wt/Bdl lbs.	Wt. Per Master
1/4	10'	25	250	20	5,000	35	706	30	601	-	-	-	-	3/8	30	601
	20'	25	500	20	10,000	71	1,412	60	1,203	-	-	-	-		60	1,203
3/8	10'	25	250	20	5,000	65	1,297	46	925	-	-	-	-	1/2	46	925
	20'	25	500	20	10,000	130	2,593	93	1,851	-	-	-	-		93	1,851
1/2	10'	25	250	20	5,000	83	1,654	68	1,358	48	966	-	-	5/8	68	1,358
	20'	25	500	20	10,000	165	3,309	136	2,717	97	1,932	-	-		136	2,717
5/8	10'	10	100	25	2,500	-	-	35	865	-	-	-	-	3/4	35	865
	20'	10	200	25	5,000	-	-	69	1,730	-	-	-	-		69	1,730
3/4	10'	10	100	25	2,500	60	1,489	43	1,065	31	772	-	-	7/8	43	1,065
	20'	10	200	25	5,000	119	2,978	85	2,131	62	1,544	-	-		85	2,131
1	10'	5	50	40	2,000	39	1,557	31	1,222	22	865	-	-	1 1/8	31	1,222
	20'	5	100	40	4,000	78	3,113	61	2,443	43	1,730	-	-		61	2,443
1 1/4	10'	5	50	20	1,000	48	961	41	822	32	635	33	650	1 3/8	41	822
	20'	5	100	20	2,000	96	1,922	82	1,645	63	1,269	65	1,301		82	1,645
1 1/2	10'	5	50	20	1,000	64	1,271	54	1,070	44	875	40	810	1 5/8	54	1,070
	20'	5	100	20	2,000	127	2,543	107	2,140	84	1,751	81	1,620		107	2,140
2	10'	5	50	10	500	96	960	82	816	68	681	53	533	2 1/8	82	816
	20'	5	100	10	1,000	192	1,921	163	1,631	136	1,362	107	1,066		163	1,631